
## LOAD DATASHEET



## 1.85MM MALE LOAD

## 1.85-J-03-2W



## \*Dimensions are in mm

| Configuration                   |                   |  |
|---------------------------------|-------------------|--|
| Connector 1 Type                | 1.85mm Male       |  |
| Connector 1 Impedance           | 50 Ohms           |  |
| Connector 1 Polarity            | Standard          |  |
| <b>Electrical Specification</b> | าร                |  |
| Frequency                       | DC to 67 GHz      |  |
| Insertion Loss (dB)             | None              |  |
| VSWR /Return Loss               | 1.45 to 67 GHz    |  |
| Power                           | 2W                |  |
| <b>Materials Information</b>    |                   |  |
| Center Contact                  | Brass Gold Plated |  |
| Outer Contact                   | Stainless Steel   |  |
| Body                            | Stainless Steel   |  |
| Dielectric                      | PEI               |  |
| <b>Environmental Data</b>       |                   |  |
| Temperature Range               | -55°C to +125°C   |  |
| 2011/65/EU(RoHS)                | Compliant         |  |

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

| Gwave Technology Inc.   |  |
|---|--|
| 4th Floor, New Material Plaza, Yongfeng Hi-Tech Base, Haidian |  |
| District, Beijing , China (100094) www.gwave-tech.com         |  |

Tel.: +86 10 86484190 Fax: +86 10 86484190-0 email: gwave@gwave-tech.com Page

1/1