

B ATTENUATORS

SMA, General Purpose, DC - 18 GHz, 2 Watts

SPECIFICATIONS:

Models: 9023

RoHS
Compliant

AEROFLEX
A passion for performance.

Electrical:

Frequency Range _____ DC - 18.0 GHz

Standard dB Values* _____ 0 - 10, 12, 15, 20, 30, 40, 50 & 60 dB

Attenuation Accuracy _____ In 1 dB Increments

0 - 12 dB _____ ±0.75 dB

13 - 20 dB _____ ±1.00 dB

21 - 40 dB _____ ±1.50 dB

41 - 60 dB _____ ±2.00 dB

VSWR

DC - 4 GHz _____ 1.20:1 Max.

4 - 12.4 GHz _____ 1.40:1 Max.

12.4 - 18 GHz _____ 1.60:1 Max.

Input Power _____ 2 Watts Avg. @ 25°C

Derated Linearly to 0.5 Watts @ +125°C

Peak Power _____ 250 Watts Max.

(5uSec Pulse, .05% Duty Cycle)

Impedance _____ 50 Ohms


Operating Temp Range _____ -65°C to +125°C

Mechanical:

SMA Connectors _____ Passivated Stainless Steel

Mates with MIL-STD-348

Conductors _____ Gold Plated Beryllium Copper



Base Model Number	Connector Configuration	LENGTH			
		0 - 30 & 40 dB		31 - 60 dB (Except 40 dB)	
		Inches	Millimeters	Inches	Millimeters
9023-XX	Male/Female	1.21 ±.03	[30.7 ±0.8]	1.49 ±.03	[37.8 ±0.8]

HOW TO ORDER:

Model Number: **9023-XX**

Base Number dB Value

Ordering Examples:

Model Number: **9023-20**
20 dB; SMA - Male/Fem

Note: Dimensions in Brackets are Expressed in Millimeters and are for Reference Only.

*Other dB values are also available.

9023: REV G (M)

AEROFLEX
INMET

Aeroflex / Inmet, Inc. • 300 Dino Drive, Ann Arbor, MI 48103 • U.S.A.
888-244-6638 or 734-426-5553 • FAX: 734-426-5557
www.aeroflex-inmet.com • inmet-sales@eroflex.com