



\*Dimensions are in mm

## Configuration

|                       |            |
|-----------------------|------------|
| Connector 1 Type      | BNC Male   |
| Connector 1 Impedance | 50 Ohms    |
| Connector 1 Polarity  | Standard   |
| Connector 2 Type      | BNC Female |
| Connector 2 Impedance | 50 Ohms    |
| Connector 2 Polarity  | Standard   |
| Connector 3 Type      | BNC Female |
| Connector 3 Impedance | 50 Ohms    |
| Connector 3 Polarity  | Standard   |
| Adapter Body Style    | Tee        |

## Electrical Specifications

|           |             |
|-----------|-------------|
| Frequency | DC to 3 GHz |
|-----------|-------------|

## Materials Information

|                |                     |
|----------------|---------------------|
| Center Contact | CuBe Gold Plated    |
| Outer Contact  | Brass Nickel Plated |
| Body           | Brass Nickel Plated |
| Dielectric     | PTFE                |

## Environmental Data

|                   |                 |
|-------------------|-----------------|
| Temperature Range | -55°C to +165°C |
| 2002/95/EC(RoHS)  | Compliant       |

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.