



* Label and Shrinking tube design depend on customer's request.

Configuration

Connector 1 Type	N Female
Connector 1 Body Style	Straight
Body Material and Plating	Brass Nickel Plated
Connector 1 Mount Method	None
Connector 2 Type	N Female
Connector 2 Body Style	Straight
Body Material and Plating	Brass Nickel Plated
Connector 2 Mount Method	4 Hole Flange
Cable Type	GUT-141(Copper)

Electrical Specifications

Impedance	50 Ω
Frequency	DC to 6 GHz
Return Loss/VSWR	1.3 to 6 GHz
Phase Stability vs. Flexure	N/A
Amplitude Stability	N/A
Shielding Effectiveness	<-100dB @ 1GHz
Phase Matching	On request
Signal Delay	On request
Power Handling	182watt @ 5GHz at sea level,VSWR1.0

Environmental Data

Temperature Range	-40°C to +125°C
2011/65/EU(RoHS)	Compliant

Cable Specifications

Center Conductor	Silver plated copperweld
Dielectric	Solid PTFE
Jacket	Copper
Capacitance(pF/m)	95.1
Velocity of propagation(%)	70
Min. bending radius(mm)	10
Jacket Diameter(mm)	3.58±0.05

Part Number List

Part Number	Length [mm]	Insertion Loss ≤(dB)	
		1Hz	5GHz
GA720-NFNFF-1000	1000±10	0.48	1.11
GA720-NFNFF-800	800±8	0.41	0.93
GA720-NFNFF-600	600±6	0.33	0.75
GA720-NFNFF-500	500±5	0.29	0.655
GA720-NFNFF-400	400±5	0.255	0.56
GA720-NFNFF-300	300±5	0.22	0.47
GA720-NFNFF-260	260±5	0.198	0.436
GA720-NFNFF-200	200±5	0.176	0.382
GA720-NFNFF-100	100±5	0.138	0.291

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.