



* Label and Shrinking tube design depend on customer's request.

Configuration

Connector 1 Type	N Male
Connector 1 Body Style	Straight
Body Material and Plating	Brass Trimetal Plated
Connector 1 Mount Method	None
Connector 2 Type	N Male
Connector 2 Body Style	Straight
Body Material and Plating	Brass Trimetal Plated
Connector 2 Mount Method	None
Cable Type	GUT-250-Form-FEP

Electrical Specifications

Impedance	50 Ω
Frequency	DC to 3 GHz
Return Loss/VSWR	1.2 to 3 GHz
PIM	<-120dB@ 1GHz
Shielding Effectiveness	\leq 163dBc@ 2x20W at 800MHz~2500MHz
Power Handling	110watt @ 2.2GHz at sea level,VSWR1.0

Environmental Data

Temperature Range	-40°C to +125°C
2002/95/EC(RoHS)	Compliant

Cable Specifications

Center Conductor	Silver plated copper
Dielectric	Solid PTFE
Jacket	FEP
Capacitance(pF/m)	94
Velocity of propagation(%)	70
Min. bending radius(mm)	40
Jacket Diameter(mm)	7.20

Part Number List

Part Number	Length [mm]	Insertion Loss \leq (dB)	
		1GHz	3GHz
GA732-NMNM-6000	6000 \pm 30	1.74	3.38
GA732-NMNM-5000	5000 \pm 30	1.48	2.85
GA732-NMNM-4000	4000 \pm 20	1.23	2.38
GA732-NMNM-3000	3000 \pm 20	0.97	1.86
GA732-NMNM-1135	3000 \pm 20	0.49	0.89
GA732-NMNM-200	200 \pm 10	0.06	0.12
GA732-NMNM-150	150 \pm 10	0.05	0.09

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.