



\* Label and Shrinking tube design depend on customer's request.

<b>Configuration</b>	
Connector 1 Type	SMA Male
Connector 1 Body Style	Straight
Body Material and Plating	Passivated Staindless Steel
Connector 1 Mount Method	None
Connector 2 Type	SMA Male
Connector 2 Body Style	Straight
Body Material and Plating	Passivated Staindless Steel
Connector 2 Mount Method	None
Cable Type	205A Series
<b>Electrical Specifications</b>	
Impedance	50 $\Omega$
Frequency	DC to 26.5 GHz
Return Loss/VSWR	1.25 to 18 GHz 1.30 to 26.5 GHz
Phase Stability vs. Flexure	N/A
Amplitude Stability	N/A
Shielding Effectiveness	<-100dB @ 1GHz
Phase Matching	On Request
Signal Delay	On Request
Power Handling	350Watt @ 5GHz at Sea Level,VSWR1.0
<b>Environmental Data</b>	
Temperature Range	-40°C to +165°C
2002/95/EC(RoHS)	Compliant

**Cable Specifications**

Center Conductor	Silver plated copper
Dielectric	Low Density PTFE
Jaket	FEP
Capacitance(pF/m)	80.4
Velocity of propagation(%)	83
Min. bending radius(mm)	6.35
Jacket Diameter(mm)	5.21±0.13

**Armor Specifications**

Armor Type	Polyurethane Jacket Over Braid Stainless Steel Spiral
Min. bending radius(mm)	25.4
Diameter(mm)	10.8

**Part Number List**

Part Number	Length [mm]	Insertion Loss ≤(dB)			
		3GHz	6GHz	10GHz	18GHz
GAA3-SMMSMM-12000A1	12000±30	4.99	7.13	9.31	12.69
GAA3-SMMSMM-10000A1	10000±30	4.18	5.98	7.81	10.64
GAA3-SMMSMM-8000A1	8000±30	3.38	4.83	6.29	8.58
GAA3-SMMSMM-6000A1	6000±30	2.58	3.68	4.79	6.53
GAA3-SMMSMM-3000A1	3000±30	1.37	1.96	2.54	3.46
GAA3-SMMSMM-2000A1	2000±20	0.96	1.37	1.79	2.43
GAA3-SMMSMM-1500A1	1500±15	0.76	1.08	1.42	1.92
GAA3-SMMSMM-1200A1	1200±12	0.64	0.911	1.19	1.61
GAA3-SMMSMM-1000A1	1000±10	0.56	0.796	1.04	1.41
GAA3-SMMSMM-600A1	600±10	0.397	0.566	0.736	0.997
GAA3-SMMSMM-500A1	500±10	0.357	0.51	0.66	0.894

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.