


GT3657, FLEXIBLE CABLE,
2.4MM(FEMALE)- GPPO(FEMALE)**GAU12V-24FGPPF-XXX**

2.4mm Female

GPPO Female

* Label and Shrinking tube design depend on customer's request.

Configuration

Connector 1 Type	2.4mm Female
Connector 1 Body Style	Straight
Body Material and Plating	Passivated Stainless Steel
Connector 1 Mount Method	None
Connector 2 Type	GPPO(MINI-SMP) Female
Connector 2 Body Style	Straight
Body Material and Plating	CuBe Gold Plated
Connector 2 Mount Method	None
Cable Type	GT3657

Electrical Specifications

Impedance	50 Ω
Frequency	DC to 50 GHz
Return Loss/VSWR	10dB
Phase Stability vs. Flexure	N/A
Amplitude Stability	N/A
Shielding Effectiveness	<-90dB @ 1GHz
Phase Matching	On request
Signal Delay	On request

Environmental Data

Temperature Range	-40°C to +125°C
2011/65/EU(RoHS)	Compliant

Cable Specifications

Center Conductor	Sliver Plated Copper
Dielectric	ePTFE
Jacket	Gray PFA
Velocity of propagation(%)	75
Min. bending radius(mm)	8
Jacket Diameter(mm)	1.5

Part Number List

Part Number	Length [mm]	Insertion Loss $\leq$ (dB)				
		3GHz	6GHz	18GHz	40GHz	50GHz
GAU12V-24FGPPF-100	100 $\pm$ 5	0.55	0.77	1.35	2.03	2.27
GAU12V-24FGPPF-200	200 $\pm$ 5	0.74	1.06	1.85	2.79	3.13
GAU12V-24FGPPF-300	300 $\pm$ 5	0.94	1.34	2.35	3.55	3.98
GAU12V-24FGPPF-500	500 $\pm$ 5	1.34	1.90	3.35	5.07	5.70
GAU12V-24FGPPF-1000	1000 $\pm$ 10	2.33	3.32	5.84	8.87	9.98

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.