


MODEL No:

MINI-FAKRA-T1372

NOTE:Information herein is believed by Gwave to be accurate.However,Gwave assumes no responsibility for any omissions or errors inaccuracies for its use or for any infringements of patents or other rights of third parties that may result from its use.Data is intended for informational purpose only and does not constitute a contract of sale or any express or implied warranty,including any warranty of merchat ability or fitness for a particular purpose.

RoHS Outline Drawing

外观图



MINI FAKRA 四合一接头	FAKRA接头
P1	L1-FAKRA Z型公头-500MM
P2	L2-FAKRA Z型公头-500MM
P3	L3-FAKRA Z型公头-500MM
P4	L4-FAKRA Z型公头-500MM

NO	项目	要求详细内容
1	性能要求	1. 频率Frequency: 0~6GHz 2. 阻抗Impedance: 50Ω
2	包装要求	1PCS/扎, 5扎/PE袋, 即5PCS/袋

备注: 1. *表示重点管控尺寸 3. 产品符合RoHS2.0和REACH标准
2. ()表示需检测的尺寸

NO	DESCRIPTION描述	SPECIFICATION规格	QTY数量
4	THIMBLE 热缩管	黑色 L=18MM	4
3	CABLE 线材	RG174LL L=500MM	4
2	FAKRA Z型公头	Z型 水蓝色	4
1	MINI FAKRA 四合一Z型母头	Z型 水蓝色	1

1.ALL DIMENSIONS ARE IN MM.AII ANGLES ARE IN DEGREES.
NOTES:UNLESS OTHERWISE SPECIFIED.

REV A	PROTOTYPE RELEASE	DATE:	APRVD: DATE:
----------	----------------------	-------	-----------------

Gwave
Technical Confirmation Form

TITLE:
MINI-FAKRA-T1372

DRN BY:	DATE:	DWG NO.	REV. 1.0
SHEET:1 OF 1			