



*Dimensions are in mm

Configuration

| | |
|----------------------------|--------------|
| Connector 1 Type | MMCX Male |
| Connector 1 Impedance | 50 Ohms |
| Connector 1 Polarity | Standard |
| Body Style | Straight |
| Connector Mount Method | 50 Ohms |
| Connector 2 Interface Type | RG316 RG316D |
| Cable Attachment Method | Solder&Crimp |

Electrical Specifications

| | |
|---------------------|---------------------------------------|
| Frequency | DC to 3 GHz |
| Insertion Loss (dB) | $\leq 0.1 \times \text{sqrt}(f_GHz)$ |
| VSWR /Return Loss | 1.3 |

Materials Information

| | |
|----------------|-------------------|
| Center Contact | Brass Gold Plated |
| Outer Contact | Brass Gold Plated |
| Body | Brass Gold Plated |
| Dielectric | PTFE |

Environmental Data

| | |
|-------------------|-----------------|
| Temperature Range | -40°C to +165°C |
| 2002/95/EC(RoHS) | Compliant |

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty of our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.