



*Dimensions are in mm

Configuration

| | |
|------------------------|-------------|
| Connector 1 Type | SMA Male |
| Connector 1 Impedance | 50 Ohms |
| Connector 1 Polarity | Standard |
| Connector 2 Type | SMA Female |
| Connector 2 Impedance | 50 Ohms |
| Connector 2 Polarity | Standard |
| Connector Mount Method | None |
| Adapter Body Style | Right Angle |

Electrical Specifications

| | |
|---------------------|--|
| Frequency | DC to 18 GHz |
| Insertion Loss (dB) | $\leq 0.1 \times \text{Sqrt.}(f_GHz)$ |
| VSWR /Return Loss | 1.25 to 8 GHz |

Materials Information

| | |
|----------------|-------------------|
| Center Contact | CuBe Gold Plated |
| Outer Contact | Brass Gold Plated |
| Body | Brass Gold Plated |
| Dielectric | PTFE |

Environmental Data

| | |
|-------------------|-----------------|
| Temperature Range | -40°C to +125°C |
| 2011/65/EU(RoHS) | Compliant |

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.