
CONNECTOR DATASHEET



7/16(FEMALE) CONNECTOR FOR FLEXIBLE CABLE

7/16-KFC08



*Dimensions are in mm

| Configuration | |
|----------------------------|---------------------------|
| Connector 1 Type | 7/16 Female |
| Connector 1 Impedance | 50 Ohms |
| Connector 1 Polarity | Standard |
| Body Style | Straight |
| Connector Mount Method | 4 Hole Flange |
| Connector 2 Interface Type | 1/2" Super Flexible Cable |
| Cable Attachment Method | Solder |
| Electrical Specification | ns |
| Frequency | DC to 3 GHz |
| Insertion Loss (dB) | ≤ 0.1 xSqt.(f_Ghz) |
| Return loss/VSWR | 1.25 |
| Materials Information | 1 |
| Centre Contact | CuSn Silver Plated |
| Outer Contact | Brass cusnzn3 Plated |
| Body | Brass cusnzn3 Plated |
| Dielectric | PTFE |
| Environmental Data | |
| Temperature Range | -55°C to +155°C |
| 2002/95/EC(RoHS) | Compliant |

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

Gwave Technology Co.,Ltd.

No.33 Building,Hanjiachuan Yard,Haidian District,Beijing
China(100094) www.gwave-tech.com

Tel.: +86 10 62450051/52 Fax: +86 10 62450053 Email: gwave@gwave-tech.com Page

1 / 1