



* Label and Shrinking tube design depend on customer's request.

Configuration

Connector 1 Type	2.92mm Male
Connector 1 Body Style	Straight
Body Material and Plating	Passivated Stainless Steel
Connector 1 Mount Method	None
Connector 2 Type	2.92mm Female
Connector 2 Body Style	Straight
Body Material and Plating	Passivated Stainless Steel
Connector 2 Mount Method	4 Hole Flange
Cable Type	UT-085

Electrical Specifications

Impedance	50 Ω
Frequency	DC to 40GHz
Return Loss/VSWR	1.35 to 40 GHz
Shielding Effectiveness	<-130dB @ 1GHz
Phase Matching	On Request
Signal Delay	On Request
Power Handling	162.5Watt @ 1GHz at Sea Level,VSWR1.0

Environmental Data

Temperature Range	-45°C to +125°C
RoHS	Compliant

Cable Specifications

Center Conductor	Silver plated copper
Dielectric	Solid extruded PTFE
Outer Conductor	Copper
Capacitance(pF/m)	95.2
Velocity of propagation(%)	70
Min. bending radius(mm)	6
Jacket Diameter(mm)	2.2
Weight(kg/100m)	2.13

Part Number List

Part Number	Length [mm]	Insertion Loss ≤(dB)			
		3GHz	10GHz	18GHz	40G
GA710-292M292FF-1000	1000±10	1.33	2.71	3.65	6.92
GA710-292M292FF-500	500±10	0.785	1.42	2.15	3.82
GA710-292M292FF-300	300±10	0.53	0.96	1.49	2.56
GA710-292M292FF-200	200±5	0.404	0.74	1.16	1.94
GA710-292M292FF-100	100±5	0.27	0.52	0.83	1.32

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.