


086 SERIES, FLEXIBLE CABLE,  
SMA(FEMALE)- GPPO(MINI-SMP)(FEMALE)**GA711-SMFGPPWF-XXX**

\* Label and Shrinking tube design depend on customer's request.

<b>Configuration</b>	
Connector 1 Type	SMA Female
Connector 1 Body Style	Straight
Body Material and Plating	Brass Gold Plated
Connector 1 Mount Method	None
Connector 2 Type	GPPO(Mini-SMP) Female
Connector 2 Body Style	Right Angle
Body Material and Plating	CuBe Gold Plated
Connector 2 Mount Method	None
Cable Type	086 Series
<b>Electrical Specifications</b>	
Impedance	50 $\Omega$
Frequency	DC to 26.5GHz
Return Loss/VSWR	12dB to 18 GHz
Shielding Effectiveness	<-100dB @ 1GHz
Phase Matching	On Request
Signal Delay	On Request
Power Handling	141.4Watt @ 1GHz at Sea Level,VSWR1.0
<b>Environmental Data</b>	
Temperature Range	-45°C to +165°C
RoHS	Compliant

### Cable Specifications

Center Conductor	Silver plated copper
Dielectric	Solid extruded PTFE
Jaket	None
Capacitance(pF/m)	94
Velocity of propagation(%)	70
Min. bending radius(mm)	6
Jacket Diameter(mm)	2.2

### Part Number List

Part Number	Length [mm]	Insertion Loss ≤(dB)			
		5GHz	10GHz	20GHz	26.5GHz
GA711-SMFGPPWF-1000	1000±10	1.7	2.5	3.8	4.7
GA711-SMFGPPWF-800	800±8	1.4	2.06	3.14	3.86
GA711-SMFGPPWF-500	500±5	0.95	1.42	2.15	2.61
GA711-SMFGPPWF-300	300±5	0.65	0.96	1.49	1.76
GA711-SMFGPPWF-260	260±5	0.59	0.87	1.35	1.59
GA711-SMFGPPWF-200	200±5	0.51	0.74	1.16	1.34
GA711-SMFGPPWF-100	100±5	0.35	0.52	0.83	0.92

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.