



* Label and Shrinking tube design depend on customer's request.

Configuration	
Connector 1 Type	3.5mm Male
Connector 1 Body Style	Straight
Body Material and Plating	Passivated Staindless Steel
Connector 1 Mount Method	None
Connector 2 Type	3.5mm Female
Connector 2 Body Style	Straight
Body Material and Plating	Passivated Staindless Steel
Connector 2 Mount Method	None
Cable Type	205A Series
Electrical Specifications	
Impedance	50 Ω
Frequency	DC to 26.5 GHz
Return Loss/VSWR	1.35 to 26.5 GHz
Phase Stability vs. Flexure	1°@ 10GHz,2°@ 18GHz,
Amplitude Stability	N/A
Shielding Effectiveness	<-100dB @ 1GHz
Phase Matching	On request
Signal Delay	On request
Power Handling	350watt @ 5GHz at sea level,VSWR1.0
Environmental Data	
Temperature Range	-40°C to +80°C
2002/95/EC(RoHS)	Compliant

Cable Specifications

Center Conductor	Silver plated copper
Dielectric	Low Density PTFE
Jacket	FEP
Capacitance(pF/m)	80.4
Velocity of propagation(%)	83
Min. bending radius(mm)	6.35
Jacket Diameter(mm)	5.21±0.13

Armor Specifications

Armor Type	Polyurethane Jacket Over Braid Stainless Steel Spiral
Min. bending radius(mm)	25.4
Diameter(mm)	10.8

Part Number List

Part Number	Length [mm]	Insertion Loss ≤(dB)			
		6GHz	10GHz	18GHz	26.5GHz
GAA3-35M35F-10000A1	10000±50	5.98	7.82	10.64	13.1
GAA3-35M35F-5000A1	5000±50	3.11	4.05	5.51	6.78
GAA3-35M35F-4000A1	4000±40	2.53	3.31	4.48	5.52
GAA3-35M35F-3000A1	3000±30	1.95	2.54	3.46	4.26
GAA3-35M35F-2000A1	2000±20	1.37	1.79	2.45	2.98
GAA3-35M35F-1000A1	1000±10	0.79	1.04	1.41	1.73
GAA3-35M35F-800A1	800±10	0.68	0.89	1.22	1.48
GAA3-35M35F-500A1	500±10	0.57	0.66	0.92	1.12
GAA3-35M35F-200A1	200±10	0.36	0.47	0.59	0.77

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.