



* Label and Shrinking tube design depend on customer's request.

Configuration

Connector 1 Type	1.0mm Male
Connector 1 Body Style	Straight
Body Material and Plating	Passivated Stainless Steel
Connector 1 Mount Method	None
Connector 2 Type	1.0mm Male
Connector 2 Body Style	Straight
Body Material and Plating	Passivated Stainless Steel
Connector 2 Mount Method	None
Cable Type	U20 Series

Electrical Specifications

Impedance	50 Ω
Frequency	DC to 110 GHz
Return Loss/VSWR	1.44 to 110 GHz
Phase Stability vs. Flexure	N/A
Amplitude Stability	N/A
Shielding Effectiveness	>90dB
Phase Matching	On request
Signal Delay	On request

Environmental Data

Temperature Range	-55°C to +125°C
2011/65/EU(RoHS)	Compliant

Cable Specifications

Center Conductor	Silver plated copper
Dielectric	LD PTFE
Jacket	FEP
Velocity of propagation(%)	76
Min. bending radius(mm)	20
Jacket Diameter(mm)	2.0

Part Number List

Part Number	Length [mm]	Insertion Loss ≤(dB)					
		6GHz	18GHz	26.5GHz	40GHz	67GHz	110GHz
GAU20-10M10M-1000	1000±10	2.96	5.21	6.38	7.93	10.44	13.49
GAU20-10M10M-800	800±5	2.39	4.21	5.15	6.40	8.44	10.86
GAU20-10M10M-600	600±5	1.82	3.21	3.93	4.88	6.43	8.23
GAU20-10M10M-400	400±5	1.26	2.21	2.71	3.36	4.43	5.61
GAU20-10M10M-200	200±3	0.69	1.22	1.49	1.84	2.42	2.98
GAU20-10M10M-150	150±3	0.55	0.97	1.19	1.46	1.92	2.32

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.