
ADAPTOR DATASHEET



N(FEMALE)-N(FEMALE) TEE ADAPTOR

N-KKK



*Dimensions are in mm

Configuration	
Configuration	
Connector 1 Type	N Female
Connector 1 Impedance	50 Ohms
Connector 1 Polarity	Standard
Connector 2 Type	N Female
Connector 2 Impedance	50 Ohms
Connector 2 Polarity	Standard
Connector 3 Type	N Female
Connector 3 Impedance	50 Ohms
Connector 3 Polarity	Standard
Adapter Body Style	Tee
Electrical Specification	ons
Frequency	DC to 3 GHz
Materials Information	n
Center Contact	CuBe Gold Plated
Outer Contact	Brass Nickel Plated
Body	Brass Nickel Plated
Dielectric	PTFE
Environmental Data	
Temperature Range	-55°C to +165°C
2002/95/EC(RoHS)	Compliant

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

Gwave Technology Co.,Ltd.

No.33 Building,Hanjiachuan Yard,Haidian District,Beijing
China(100094) www.gwave-tech.com

Tel.: +86 10 62450051/52 Fax: +86 10 62450053 Email: gwave@gwave-tech.com Page

1/1