



\* Dimensions are in mm.

## Configuration

Connector 1 Type	SMA Female
Connector 1 Impedance	50 Ohms
Connector 1 Polarity	Standard
Connector 2 Type	GPO(SMP) Male
Connector 2 Impedance	50 Ohms
Connector 2 Polarity	Standard
Connector Mount Method	None
Adapter Body Style	Straight

## Electrical Specifications

Frequency	DC to 26.5 GHz
Insertion Loss (dB)	$\leq 0.1 \times \text{Sqrt.}(f\_GHz)$
Return Loss/VSWR	$\leq 1.2 @ DC \sim 18GHz$ ; $\leq 1.3 @ 18 \sim 26.5GHz$
Dielectric Withstanding Voltage	500V(rms)
Insulation Resistance	$\geq 1000M\Omega$

## Materials Information

Center Contact	CuBe Gold Plated
Outer Contact	Passivated Stainless Steel
Dielectric	PTFE

## Environmental Data

Temperature Range	-65°C to +85°C
2011/65/EU(RoHS)	Compliant

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.