

ATTENUATORS

SMA, up to 18 GHz, 25 Watts

SPECIFICATIONS:

Models: XXB25W-XX, XXB25W-XXF & XXB25W-XXM

RoHS
Compliant

AEROFLEX
A passion for performance.

Electrical:

Frequency Range _____ DC - 18.0 GHz
 Standard Freq. Values _____ 6, 18 GHz
 Standard dB Values* _____ 3, 6, 10, 20, 30 & 40 dB
 Attenuation Accuracy DC - 6 GHz 6 - 12.4 GHz 12.4 - 18 GHz
 3 - 6 dB _____ ±0.30 dB ±0.50 dB ±0.75 dB
 7 - 20 dB _____ ±0.50 dB ±0.75 dB ±1.00 dB
 21 - 30 dB _____ ±0.75 dB ±1.00 dB ±1.25 dB
 31 - 40 dB _____ ±1.00 dB ±1.25 dB ±1.50 dB

VSWR

DC - 6 GHz _____ 1.20:1 Max.
 6 - 12.4 GHz _____ 1.30:1 Max.
 12.4 - 18 GHz _____ 1.40:1 Max.

Input Power _____ 25 Watts Avg. @ 25°C
 Derated Linearly to 5 Watts @ +125°C

Peak Power _____ 500 Watts Max.
 (5uSec Pulse, .05% Duty Cycle)

Impedance _____ 50 Ohms


Operating Temp Range _____ -65°C to +125°C

Mechanical:

SMA Connectors _____ Passivated Stainless Steel
 Mates with MILSTD-348

Conductors _____ Gold Plated Beryllium Copper

Housing _____ Anodized Aluminum



END VIEW
TYPICAL

Units must be Mounted in such a way as to Allow for Free Air Flow Around fins to Insure Performance

Model Number: **XXB25W-XX**

Male/Female Connectors

Length: 3.79 ±.05 [96.3 ±1.3]

Pictured

Model Number: **XXB25W-XXF**


Female/Female Connectors

Length: 3.66 ±.05 [93.0 ±1.3]

Model Number: **XXB25W-XXM**

Male/Male Connectors

Length: 3.92 ±.05 [99.6 ±1.3]



HOW TO ORDER:

Model Number: **XXB25W-XXV**

Freq. Range
 6 = DC - 6 GHz
 18 = DC - 18 GHz

Connector Configuration
 = Male/Female
 F = Fem/Fem
 M = Male/Male

dB Value

Ordering Examples:

Model Number: **18B25W-20**
 DC - 18 GHz; 20 dB; SMA - Male/Fem

Model Number: **6B25W-03F**
 DC - 6 GHz; 3 dB; SMA - Fem/Fem

Note: Dimensions in Brackets are Expressed in Millimeters and are for Reference Only.

*Other dB values, units that operate over a more specific frequency band and/or offer very low return loss (VSWR) are also available.

XXB25W-ATT: REV K (M)

AEROFLEX
INMET

Aeroflex / Inmet, Inc. • 300 Dino Drive, Ann Arbor, MI 48103 • U.S.A.
 888-244-6638 or 734-426-5553 • FAX: 734-426-5557
 www.aeroflex-inmet.com • inmet-sales@aeroflex.com