

TERMINATIONS

Type N Male, DC-6.0 GHz, 2 Watts

SPECIFICATIONS:


Models: 3202-NMY, 3206-NMY

Electrical:

Frequency Range _____ DC - 6.0 GHz
 VSWR _____ See Below
 Impedance _____ 50 Ohms
 Power
 Average _____ 2 Watts
 Peak _____ 500 Watts Maximum
 (1uSec Pulse, .01% Duty Cycle)
 Operating Temp Range _____ -55°C to +125°C
 2 Watt Avg. @ +25°C Derated Linearly
 to 10% of Rated Power @ +125°C

Mechanical:

Connectors & Housing _____ Brass and/or Zinc Alloy
 Conductors _____ Gold Plated Beryllium Copper
 ALL SOLDERED CONSTRUCTION FOR
 MAXIMUM RELIABILITY.




CHAIN DETAIL

Model Number: 3202-NMY

Frequency Range _____ DC - 2.5 GHz
 VSWR
 DC - 1.0 GHz _____ 1.05:1 MAX.
 1.0 - 2.5 GHz _____ 1.10:1 MAX.

Model Number: 3206-NMY

Frequency Range _____ DC - 6.0 GHz
 VSWR
 DC - 1.0 GHz _____ 1.05:1 MAX.
 1.0 - 6.0 GHz _____ 1.10:1 MAX.



HOW TO ORDER:

Model Number: **320X-NMY**

Frequency Range | Style
 2 = DC - 2.5 GHz | = No Chain
 6 = DC - 6 GHz | C = Chain Included

Ordering Examples:

Model Number: **3202-NMC**
 DC - 2.5 GHz; Type N Male; Chain Included

Model Number: **3206-NM**
 DC - 6 GHz; Type N Male; No Chain

Note: Dimensions in Brackets are Expressed in Millimeters and are for Reference Only.
 Design specifications are subject to change without notice.
 Contact factory for technical specifications before purchasing or use.

3204-NM: REV B (M)



Aeroflex / Inmet, Inc. • 300 Dino Drive, Ann Arbor, MI 48103 • U.S.A.
 888-244-6638 or 734-426-5553 • FAX: 734-426-5557
 www.aeroflex-inmet.com • inmet-sales@eroflex.com