

Attenuators

Type N, up to 4 GHz, 200 Watts

SPECIFICATIONS:

Models: XN200W-XX, XN200W-XXF, XN200W-XXM

RoHS
Compliant

AEROFLEX
A passion for performance.

Electrical:

Frequency Range _____ DC - 4 GHz
Standard Freq. Values _____ 2.5 & 4 GHz
Standard dB Values _____ 3, 6, 10, 20, 30 & 40 dB
Attenuation Accuracy DC-1.5 GHz 1.5-2.5GHz 2.5-4GHz
3 & 6 dB _____ ± 0.50 dB _____ ± 0.50 dB _____ ± 0.75 dB
10, 20, 30 & 40 dB _____ ± 0.75 dB _____ ± 1.0 dB _____ ± 1.5 dB

Input VSWR (Max.)

3, 6, 10 & 20 dB _____ 1.15:1 _____ 1.25:1 _____ 1.35:1
30 & 40 dB _____ 1.15:1 _____ 1.25:1 _____ 1.50:1

Input Power _____ 200 Watts Avg. @ +25°C
Derated Linearly to 40 Watts @ +125°C

Peak Power _____ 2 kW Max.
(5uSec Pulse, .05% Duty Cycle)

Impedance _____ 50 Ohms

Operating Temp. Range _____ -54°C to +125°C

Mechanical:

Type N Connectors _____ Passivated Stainless Steel

Notes with MIL-STD-348

Conductors _____ Gold Plated Beryllium Copper

Housing _____ Anodized Aluminum

Note: Units are unidirectional. Units must be positioned in such a way as to allow free air flow around fins to assure performance.

Model Number: **XN200W-XX**

Male/Female Connectors

Length: 8.35 $\pm$ 10 [212.09 $\pm$ 2.54]

Pictured

Model Number: **XN200W-XXF**


Female/Female Connectors

Length: 8.44 $\pm$ 10 [214.38 $\pm$ 2.54]

Model Number: **XN200W-XXM**

Male/Male Connectors

Length: 8.28 $\pm$ 10 [210.31 $\pm$ 2.54]



HOW TO ORDER:

Model Number: **XN200W-XXY**

Freq. Range _____
2 = DC - 2.5 GHz
4 = DC - 4 GHz

Connector Configuration
= Male/Female
F = Fem/Fem
M = Male/Male

dB Value

Ordering Examples:

Model Number: **2N200W-10**
DC - 2.5 GHz, 10 dB; Type N - Male/Fem

Model Number: **2N200W-40F**
DC - 2.5 GHz, 40 dB; Type N - Fem/Fem

Model Number: **4N200W-30M**
DC - 4 GHz, 30 dB; Type N - Male/Male

Note: Dimensions in Brackets are Expressed in Millimeters and are for Reference Only.
Design, specifications are subject to change without notice. Contact factory for technical specifications before purchasing and/or use.

XN200W-ATT: REV H

AEROFLEX
INMET

Aeroflex / Inmet, Inc. • 300 Dino Drive, Ann Arbor, MI 48103 • U.S.A.
888-244-6638 or 734-426-5553 • FAX: 734-426-5557
www.aeroflex-inmet.com • inmet-sales@eroflex.com